



**NOTES:**

1. SPACING OF POSTS USING HOG WIRE WITH APPROVED EROSION CONTROL FABRICS TO BE 8'-0" ON CENTER.
  2. SPACING OF POSTS WITHOUT HOG WIRE USING APPROVED EROSION CONTROL FABRICS TO BE 6'-0" ON CENTER.
- POST: METAL T-POST 5'-0" OR 6'-0" IN HEIGHT DEPENDING ON FILL SLOPE (MIN 1.33 LB/LF STEEL CONSTRUCTION).
- FABRIC: 3'-0" IN WIDTH (MUST BE STANDARD SPECIFICATIONS FOR SILT FENCE – ASTM D) WITH 12" BURIED IN TRENCH.
- STONE: (IF USED) #4 WASHED STONE PLACED 1'-0" DEEP AT SILT FENCE.
1. SPLICES IN FABRIC SHOULD BE OVERLAPPED A MIN. OF 4 FT.
  2. MAXIMUM DRAINAGE AREA = 1/4 ACRE PER 100 FT OF FENCE FOR 2% OR LESS SLOPE.
  3. SILT FENCE TO BE REMOVED AFTER CONSTRUCTION IS COMPLETE AS DIRECTED BY THE CONSTRUCTION INSPECTOR.

NOT TO SCALE